(D-A083 295

AD-A083 295

MEMORANDUM REPORT ARBRL-MR-02996

POST-SHOT BLAST LOADING PREDICTIONS FOR GERMAN STRUCTURE NO. 2 DICE THROW EVENT

George A. Coulter

March 1980



US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND BALLISTIC RESEARCH LABORATORY ABERDEEN PROVING GROUND, MARYLAND

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed. Do not return it to the originator.

Secondary distribution of this report by originating or sponsoring activity is prohibited.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, Springfield, Virginia 22151.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM		
1. REPORT NUMBER 2. GOVT ACCESSION NO.			
Memorandum Report ARBRL-MR- 02996			
4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED		
Post-Shot Blast Loading Predictions for German			
Structure No. 2 - Dice Throw Event	Final		
	6. PERFORMING ORG, REPORT NUMBER		
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(8)		
George A. Coulter			
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM FLEMENT PROJECT TASK		
US Army Ballistic Research Laboratory	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 62704H		
(ATTN: DRDAR-BLT)	X99QAXSC301		
Aberdeen Proving Ground, MD 21005	001AJ		
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE		
US Army Armament Research & Development Command	MARCH 1980		
US Army Ballistic Research Laboratory	13. NUMBER OF PAGES		
(ATTN: DRDAR-BL), Aberdeen Proving Ground, MD 2100			
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)	15. SECURITY CLASS. (of this report)		
Defense Nuclear Agency Washington, DC 20305	UNCLASSIFIED		
Mashington, Do 2000	1Se. DECLASSIFICATION/DOWNGRADING SCHEDULE		
16. DISTRIBUTION STATEMENT (of this Report)			
Approved for public release; distribution unlimited	d.		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from	m Report)		
,			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse elde if necessary and identify by block number)			
Air Blast Fill Pressure			
Blast Loading Loading Pressure			
Collateral Damage Model House			
Dice Throw Event Wall Loading			
20. ABSTRACT (Continue on reverse eids if necessary and identify by block number)			
Pressure-time blast loading post-shot predictions	are presented for German		
Structure No. 2 exposed on the Dice Throw Event. Loading curves are shown			
for front, side, and interior structure locations.			
<u></u> ♣.			

TABLE OF CONTENTS

		Page
	LIST OF ILLUSTRATIONS	5
I.	INTRODUCTION	7
II.	FRONT LOADING	7
III.	INTERIOR FILL LOADING	11
IV.	SIDE LOADING	16
V.	SUMMARY AND CONCLUSIONS	17
	REFERENCES	19
	DISTRIBUTION LIST	21

LIST OF ILLUSTRATIONS

Figure		Page
1.	German structure - Dice Throw Event	8
2.	Sketch for front loading	9
3.	Front loading prediction for P-2 on German structure No. 2, Dice Throw Event	12
4.	Floor plan for German structure No. 2 on Dice Throw Event	13
5.	Fill predictions for P-8 in German structure No. 2, Dice Throw Event	14
6.	Fill prediction for P-3 in German structure No. 2, Dice Throw Event	15
7.	Prediction for P-1 outside of wall of German structure No. 2, Dice Throw Event	18

I. INTRODUCTION

The Defense Nuclear Agency (DNA) requested the Ballistic Research Laboratory (BRL) to predict after the event the pressure-time loading at selected locations for German structure No. 2 exposed on the Dice Throw Event. This structure was one of three located at different distances (and pressure levels) from the detonation of 5.7 x 10⁵ kg of ammonium nitrate-fuel oil mixture (Reference 1) at the White Sands, New Mexico test site in October 1976. Only Structure No. 2 was to be considered for these predictions. Pressure-time profiles were calculated for Structure No. 2 and are presented for a front wall position, two interior room locations, and for a ground position near to the outside of the left side wall. The measured field data obtained for the structure are displayed in graphical form with the predictions for comparison.

II. FRONT LOADING

Sketches of the structure are shown as Figures 1 and 2. They illustrate the two types of construction material used-brick and block for the left room and brick and wood for the right room. Window areas and some pertinent dimensions are shown which are needed for later use in the calculations. The relative location of the transducer P-2 is shown on the front wall (Figure 2) between the two rooms of the structure. A method follows illustrating the calculation of the front loading at this position.

As the blast wave (created from the detonation of the high explosive) reaches the front wall of the structure, reflected pressure covers the front wall. The reflected pressure loads the front wall until rarefaction waves arrive from the windows and wall edges. For the location of P-2, the first rarefaction came from the left window. Later rarefactions (from left edge, roof, right window, and right edge) decayed the remaining pressure to still lower values until stagnation pressure was reached on the front wall. Both reflected pressure and stagnation pressure are time dependent with the decay of the side-on free-field blast wave.

The method used for the loading calculation for transducer location P-2 is illustrated by the following set of equations. Ambient test conditions (Reference 1) were given as a temperature of $\rm T_1$ = 9.7° C, a pressure $\rm P_1$ = 85 kPa, a density $\rm S_1$ = 1.05 kg/m³ (calculated), and the side-on peak blast pressure of $\rm P_S$ = 25.5 kPa.




Figure 1. German structure - Dice Throw Event.




Figure 2. Sketch for front loading.

From these, an ambient sound speed, A_1 , is calculated from Equation 1:

$$A_1 = 331.62 \left(1 + \frac{T_1}{273.16}\right)^{\frac{1}{2}} = 337.4 \text{ m/s.}$$
 (1)

The first rarefaction will arrive from the window edge (D = 1.34 m) after a time,

$$TR = D/C_{ref} = 3.7 ms, \qquad (2)$$

where the sound velocity, C $_{\rm ref}$, in the reflected pressure is obtained from Equation 3 (derived from Reference 2 for γ = 1.4 for air).

$$C_{\text{ref}} = A_1 \begin{bmatrix} (8 \frac{P_S}{P_1} + 7) & (2 \frac{P_S}{P_1} + 7) \\ \hline & & 1 \end{bmatrix} = 363.4 \text{ m/s}.$$
 (3)

The loading during the period of reflected pressure is given by Equation 4,

$$P = P_{ref}(T), 0 \le T \le TR, \tag{4}$$

where

$$P_{ref} = 2P_{s} \left[\frac{7P_{1} + 4P_{s}}{7P_{1} + P_{s}} \right] = 57.3 \text{ kPa}$$
 (5)

at T=0. As the side-on blast wave pressure decays during this time, so does the reflected pressure. The value of P_{ref} at time TR is assumed to equal the reflected value for the side-on value existing at the time TR. See the tables in Reference 3 or use Equation 5 for P_{ref} (TR). P_{ref} (TR) = 54 kPa. Equation 6 is next used (Reference 4):

$$P = P_{ref}(TR) e^{-[0.232(T-TR)/TR]}$$
 (6)

for TR < T < 2.5 TR.

As later rarefactions cause additional pressure decay, Equation 7 is used:

$$P = 0.70 P_{ref}(TR) e^{-[0.36(T-2.5TR)/(TC-2.5TR)]}$$
 (7)

for 2.5 TR \leq T \leq TC, where the clearing time, TC, is given by Equation 8.

$$TC = 2.5 DR/C_{ref} = 20.6 ms$$
 (8)

where,

DR = least of WD/2 or HT,
DR = HT =
$$3.0$$
m. (9)

and

After the clearing time, the front loading pressure follows the stagnation pressure of the input blast wave:

$$P = P_{stag} (T)$$
 (10)

for

T > TC.

Figure 3 shows a plot of the predicted pressure-time loading (for P-2) as calculated by the above steps. The predicted loading is compared with the side-on input blast wave for free-field and the measured loading (from P-2) from the Dice Throw Event (Reference 5).

The predicted initial reflected pressure was not reached by the transducers. The predicted decay follows the data well until later rarefactions arrive and cause still lower pressure than predicted. After about 50 ms it is belived that the transducer began to leak internally and behaved in a differential manner at times after the transducer mount on the structure began to be loosened. This would account for a positive loading duration considerably shorter than the free-field blast wave.

III. INTERIOR FILL LOADING

Pressure-time profiles for transducer locations P-3 and P-8 (Figure 4), one in each room, were chosen for comparison to the fill predictions.

A BRL filling code reported in Reference 6 was used for the fill predictions shown in Figures 5 and 6. Input values needed for the code are ambient conditions, blast stagnation pressure (calculated from Reference 2 for input values), window openings, and volume of the rooms.

The filling code takes the stagnation pressure as a reservoir of pressure over the front wall which is the driving pressure source that fills the two rooms. The filling rate is proportional to ratio of the room volume to window area. Figure 4 lists these values for the two rooms of the structure. An orifice coefficient is included in the program to take into account choking of the flow through the openings.




Figure 3. Front loading prediction for P-2 on German structure No. 2, Dice Throw Event.




Figure 4. Floor plan for German structure No. 2 on Dice Throw Event.




Figure 5. Fill prediction for P-8 in German structure No. 2, Dice Throw Event.




Figure 6. Fill prediction for P-3 in German structure No. 2, Dice Throw Event.

As the pressure reservoir level changes, both sonic and subsonic flows are allowed for in the program. An average fill pressure is calculated for the incremented time chosen. A smooth filling curve is produced by this prediction code.

For brick and wood room (left side), the prediction follows fairly well the measured curve obtained at P-8 (Figure 5). The location was far enough into the room so that a smooth experimental filling curve resulted and matched the prediction.

A similar smooth prediction, Figure 6, made for the brick and wood room at P-3 did not match as well as before for P-8. The transducer for this room was quite close to the window opening. Diffracted waves from the original blast wave entering through the window created a non-smooth filling curve and did not agree with the prediction as well as before.

IV. SIDE LOADING

The prediction method for transducer location P-1 was taken from Reference 7. The assumption was made that this station would be representative of loading on the side wall near the ground. The side-loading pressure follows quite closely that of the free-field input blast except that a vortex from the front wall edge lowers the pressure at a given location as the vortex crosses the area. The equations below, taken from Reference 6, illustrate how this effect is taken into account.

The minimum pressure, P_{side} , caused by the vortex at a time, t_{m} , is given by Equation 11:

$$P_{\text{side}} = P_{\text{s}}(t)[4(P_{\text{s}}/P_{1})(\frac{L}{L} - 1) + 1],$$
 (11)

where $P_s(t)$ is the free-field pressure at the front wall as a function of time; P_s is the peak free-field pressure, 25.35 kPa; P_1 is the ambient pressure, 85 kPa; L is distance to the location of P-1, 2.36m; and L is the length of the side wall, 4.63m.

$$P_{side} = 10.13 \text{ kPa}$$
, (12)

at a time:

$$t_{\rm m} = L'/v = 64 \text{ ms}$$
 (13)

where v is the vortex travel velocity and is calculated from Equation 14.

$$v = (0.042 + 0.108 \frac{L}{L})U_0 = 36.7 \text{ ms},$$
 (14)

where U_0 is the blast wave front velocity. Equation 15 gives this value.

$$U_0 = A_1 \left(\frac{6}{7} \frac{P_s}{P_1} + 1\right)^{\frac{1}{2}} = 378.3 \text{ ms}$$
 (15)

The pressure loading will begin to decay when the decreasing effect of the vortex is just beginning at a time (measured from arrival at front wall),

$${}^{1}_{2}(t_{d} + t_{m}) = 35 \text{ ms}$$
 (16)

where,

$$t_{d} = L'/U_{o} = 6 \text{ ms}$$
 (17)

The effect of the vortex is felt until a time defined to be:

$$t_{m} + 15 \text{ h}'/U_{0} = 182 \text{ ms}.$$
 (18)

h' = 3.0 m the clearing height, taken as the minimum of HT or WD/2.

Figure 7 shows the pressure lowering vortex effect (solid line) plotted from arrival at P-1, together with the experimental vortex effect measured and the free-field blast wave profile. It is seen from a comparison of the curves that the prediction technique considerably over predicts the effect of the vortex at this location.

V. SUMMARY AND CONCLUSIONS

Predictions of pressure-time loading were made at several locations on German structure No. 2 exposed to the 25.35 kPa overpressure level on the Dice Throw Event. The front loading predictions and average fill loading compared favorably to the experimental records. The fill code used did not have the capability to predict the internal reflections superimposed on the average fill curve. It differed from the experimental curve obtained from the location near the window of the right room (brick and wood). The side wall prediction showed much more of a vortex effect than was measured.

In conclusion, the front loading and average fill curves can be predicted quite well, whereas the side loading prediction method needs some adjustment to account more accurately for the vortex effect.




Figure 7. Prediction for P-1 outside of wall of German structure No. 2, Dice Throw Event.

REFERENCES

- 1. "Proceedings of the Dice Throw Symposium", 21 23 June 1977, Vol 1 and Vol 3, Defense Nuclear Agency, DNA 4377P-1 and 4377P-3, July 1977.
- 2. Edward F. Greene and J. Peter Toennies, "Chemical Reaction in Shock Waves", Academic Press, Inc., New York, NY, 1964.
- 3. Joseph F. Melichar, "The Propagation of Blast Waves into Chambers", Ballistic Research Laboratories Memorandum Report No. 1920, March 1968 (AD# 672476).
- 4. George A. Coulter, "Air Shock Loading of Exterior Walls of Shelter Models", Ballistic Research Laboratories Memorandum Report No. 2118, August 1971, (AD# 729775).
- 5. C. K. Wiehle, J. R. Remple, and J. E. Beck, "Dynamic Response of Two Types of German House Construction", Stanford Research Institute POR 6966, September 15, 1977.
- 6. George A. Coulter, "Blast Loading in Existing Structures Basement Models", Ballistic Research Laboratories Memorandum Report No. 2208, August 1972 (AD# 751769).
- 7. "Design of Structures to Resist the Effects of Atomic Weapons", Headquarters, Department of the Army, Washington, DC, TM5-856-1, November 1960.

No. of Copies		No. of Copies	
12	Commander Defense Technical Info Center ATTN: DDC-DDA Cameron Station Alexandria, VA 22314	3	Director US Army Advanced BMD Technology Center ATTN: Mr. B. E. Kelley Mr. M. Capps Mr. Marcus Whitfield
3	Director of Defense Research & Engineering ATTN: DD/TWP DD/S&SS DD/I&SS AD/SW Washington, DC 20301 Director	1	P. O. Box 1500 Huntsville, AL 35807
Ü	Defense Advanced Research Projects Agency ATTN: Tech Lib NMRO PMO 1400 Wilson Boulevard Arlington, VA 22209	1	Commander US Army Ballistic Missile Defense Program Office ATTN: DACS-SAE-S, J. Shea 5001 Eisenhower Avenue Alexandria, VA 22333
5	Director Defense Nuclear Agency ATTN: STTL (Tech Lib, 2 cys) SPAS, Mr. D. Kohler DDST, Mr. P.H. Haas SPSS, Dr. G. Ullrich Washington, DC 20305	2	Commander US Army Engineer Waterways Experiment Station ATTN: Library W. Falteau P. O. Box 631 Vicksburg, MS 39180
2	Commander Field Command, DNA ATTN: FCTMOF Kirtland AFB, NM 87115	1	Commander US Army Materiel Development and Readiness Command ATTN: DRCDMD-ST 5001 Eisenhower Avenue
2	Department of Defense Explosives Safety Board ATTN: R. Perkins Dr. Tom Zaker Room GS-270, Forrestal Bldg. Washington, DC 20314	4	Alexandria, VA 22333 Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS (2 cys) P. Angelotti
1	HQDA (DAMA-AR, NCB Division) Washington, DC 20310		Mr. Demitrack Dover, NJ 07801

No. of No. of Copies Organization Copies Organization 2 Commander 3 Commander US Army Armament Materiel US Army Missile Command Readiness Command ATTN: DRDMI - R SARRI-LR, B. Morris DRDMI-YDL DRSAR-LEP-L, Tech Lib DRDMI-S, Ch Scientist Rock Island, IL 61299 Redstone Arsenal, AL 35809 1 Director 2 Commander US Army ARRADCOM US Army Tank Automotive Benet Weapons Laboratory Research & Development Cmd ATTN: DRDAR-LCB-TL ATTN: DRDTA-UL Watervliet, NY 12189 DRDTA-RHT, LT P. Hasek Warren, MI 48090 1 Commander US Army Aviation Research 1 Director and Development Command US Army Materials and ATTN: DRSAV-E Mechanics Research Center P. O. Box 209 ATTN: Technical Library St. Louis, MO 63166 Watertown, MA 02172 1 Director 1 Commander US Army Air Mobility Research US Army Foreign Science and Development Laboratory and Technology Center Ames Research Center ATTN: Research & Data Branch Moffett Field, CA 94035 220 Seventh Street, NE Charlottesville, VA 22901 1 Commander US Army Communications Rsch 3 Commander and Development Command US Army Nuclear Agency ATTN: DRDCO-PPA-SA ATTN: ATCN-W, CAPT M. Bowling Fort Monmouth, NJ 07703 CDINS-E Technical Library 1 Commander 7500 Backlick Road, Bldg. 2073 US Army Electronics Research Springfield, VA 22150 and Development Command Technical Support Activity Director 1 ATTN: DELSD-L US Army TRADOC Systems Fort Monmouth, NJ 07703 Analysis Activity ATTN: ATAA-SL, Tech Lib 4 Commander White Sands Missile Range US Army Harry Diamond Labs NM 88002 DRXDO-TI/012 ATTN: DRXDO-NP, F. Wimenitz DRXDO-NP, J. Gaul DRXDO-NP, J. Gwaltney 2800 Powder Mill Road

Adelphi, MD 20783

No. of Copies		o. of	
2	Chief of Naval Research Department of the Navy ATTN: T. Quinn, Code 461		AFOSR (OAR) Bolling AFB, DC 20332
	J. L. Warner, Code 461 Washington, DC 20360	1	RADC (Document Lib, FMTLD) Griffis AFB, NY 13440
2	Commander Naval Ship Eng'g Center ATTN: J.R. Sullivan NSEC 6105-G Technical Library Hyattsville, MD 20782		AFWL (CA, Dr. A. Guenther DYT, Charles Needham DYT, MAJ G. Gonong; S. Melzer) Kirtland AFB, NM 87117 AFCRL
4	Commander	_	L. G. Hanscom Field Bedford, MA 01730
	Naval Surface Weapons Center ATTN: Code 1224, Navy Nuclear Program Office Code 241, J. Petes Code 730, Tech Lib	1	SAMSO (Library) P.O. Box 92960 Los Angeles, CA 90009
	J. Pittman Silver Spring, MD 20910	3	AFTC (K. Rosenlof R. McBride G. Leies)
1	Commander Naval Weapons Evaluation Fac ATTN: Document Control Kirtland AFB, NM 87117	2	Patrick AFB, FL 32925 AFML (G. Schmitt, MAS; D. Schmidt)
1	Commander		Wright-Patterson AFB, OH 45433
-	Naval Civil Engineering Lab ATTN: Dr. W.A. Shaw, Code L31 Port Hueneme, CA 93041		Energy Research & Development Administration Department of Military Application ATTN: R&D Branch
3	Commander Naval Research Laboratory ATTN: M. Persechino		Library Branch, G-043 Washington, DC 20545
	G. Cooperstein Tech Lib, Code 2027 Washington, DC 20375	2	Director Los Alamos Scientific Lab ATTN: Dr. J. Taylor Technical Library
1	HQ USAFSC (DLCAW, Tech Lib) Andrews AFB Washington, DC 20331		P.O. Box 1663 Los Alamos, NM 87554

No. of Copies		No. of Copies	
1	Director, NASA ATTN: Code 04.000 Langley Research Center Langley Station Hampson, VA 23365	1	John A. Blume & Associates ATTN: Dr. John A. Blume Sheraton-Palace Hotel 100 Jessie Street San Francisco, CA 94105
1	Director NASA Scientific & Technical Information Facility ATTN: SAK/DL P.O. Box 8757	1	CALSPAN Corporation ATTN: Library P.O. Box 235 Buffalo, NY 14221
1	Baltimore/Washington International Airport, Maryland 21240	1	Effects Technology, Inc. ATTN: E. Anderson 5383 Holister Avenue Santa Barbara, CA 93105
1	National Academy of Sciences ATTN: Dr. Donald Groves 2101 Constitution Avenue, NW Washington, DC 20418	1	General Electric Co TEMPO ATTN: DASIAC 816 State Street, Drawer QQ Santa Barbara, CA 93102
1	Aerospace Corporation ATTN: Tech Information Svcs, Bldg 105, Room 2220 P.O. Box 92957 Los Angeles, CA 90009	1	General Electric Co TEMPO ATTN: Dr. Lynn Kennedy 7800 Marble Avenue, NE, Suite 5 Albuquerque, NM 87110
1	Agbabian Associates ATTN: Dr. J. Malthan 250 N. Nash Street El Segundo, CA 90245	1	H-Tech Laboratories, Inc. ATTN: B. Hartenbaum P.O. Box 1686 Santa Monica, CA 90406
1	AVCO Government Products Grou ATTN: Dr. W. Bade 201 Lowell Street Wilmington, MA 01887	ip 1	Hughes Aircraft Company Systems Development Laboratory ATTN: Dr. A. Puckett Centinela and Teale Streets Culver City, CA 92032
1	AVCO-Everett Research Lab ATTN: Technical Library 2385 Revere Beach Parkway Everett, MA 02149	1	Ion Physics Corporation ATTN: Technical Library South Bedford Street Burlington, MA 01803

No. of Copies		No. of Copies	
1	Kaman Sciences Corporation ATTN: Dr. D. Sachs 1500 Garden of the Gods Road Colorado Springs, CO 80907	1	Philco Ford Corporation Aeronutronic Division ATTN: L. K. Goodwin Newport Beach, CA 92663
1	Kaman Avidyne, Division of Kaman Sciences ATTN: Dr. J. Ray Ruetenik 83 2nd Ave, NW Industrial Park Burlington, MA 01803	2	Physics International Company ATTN: Document Control Fred Sauer 2700 Merced Street San Leandro, CA 94577
1	KETCH Corporation ATTN: Dr. Donald V. Keller 911 Pennsylvania NE Albuquerque, NM 87110	3	R&D Associates ATTN: Technical Library Jerry Carpenter Allen Kuhl P.O. Box 9695
1	Lockheed Missiles & Space Company, Inc. Division of Lockheed Aircraft Corporation ATTN: J. Nickell P.O. Box 504 Synnyvale, CA 94088	1	Marina del Rey, CA 90291 Sandia Laboratories ATTN: Dr. J. Kennedy P.O. Box 5800 Albuquerque, NM 87115
1	Management Science Associates ATTN: Kenneth Kaplan P.O. Box 239 Los Altos, CA 94022	2	Science Applications, Inc ATTN: Mr. J. W. Miller Dr. John Cockayne 8400 Westpark Drive McLean, VA 22102
1	Martin Marietta Aerospace Orlando Division ATTN: A. Ossin P.O. Box 5837 Orlando, FL 32805	1	Shock Hydrodynamics, Inc. ATTN: L. Zernow 4710-16 Vineland Avenue N. Hollywood, CA 91602
1	Maxwell Laboratories, Inc. ATTN: A. Kolb 9244 Balboa Avenue San Diego, CA 92123	1	Systems, Science & Software ATTN: Technical Library P.O. Box 1620 LaJolla, CA 92036
1	McDonnell Douglas Astronautics Corporation 5301 Bolsa Avenue Huntington Beach, CA 92647	2 s	SRI International ATTN: Dr. H. Murphy J. Remple 333 Ravenswood Avenue Menlo Park, CA 94025

No. of Copies	Organization	No. of Copies	Organization
1	Union Carbide Corporation Oak Ridge National Lab ATTN: Technical Library P.O. Box X Oak Ridge, TN 37830	1	New Mexico Institute of Mining and Technology ATTN: Mr. P. McClain Socorro, NM 87801
1	URS Research Company ATTN: Technical Library 155 Bovet Road	1	Northwestern Michigan College ATTN: Prof D.C. Kennard, Jr. Traverse City, MI 49584
	San Mateo, CA 94002	1	Southwest Research Institute ATTN: Dr. W. Baker 8500 Culebra Road
1	Battelle Memorial Institute ATTN: Technical Library 505 King Avenue		San Antonio, TX 78206
2	Columbus, Ohio 43201	1	Stevens Institute of Technology Dept of Electrical Engineering ATTN: Prof R. Geldmacher
2	Denver Research Institute University of Denver ATTN: Mr. John Wisotski P.O. Box 10127		Castle Point Station Hoboken, NJ 07039
	Denver, CO 90210	1	Research Institute of Temple University
1	Director Applied Physics Laboratory		ATTN: Technical Library Philadelphia, PA 19144
	The Johns Hopkins University Johns Hopkins Road Laurel, MD 20810	1	Texas Tech University Dept of Civil Engineering ATTN: Mr. Joseph E. Minor
1	Lovelace Rsch Institute ATTN: Dr. D. Richmond		Lubbock, TX 79409
	P.O. Box 5890 Albuquerque, NM 87108	1	University of Arkansas Department of Physics ATTN: Prof O. Zinke
1	Massachusetts Institute of Technology	1	Fayetteville, AR 72701
	Aerophysics Laboratory Cambridge, MA 02139	1	University of California Lawrence Livermore Lab Technical Information Div ATTN: Technical Library Dr. Donald N. Montan P.O. Box 808 Livermore, CA 94550

No. o Copie	_	No. of Copies O	organization
1	University of Illinois Consulting Engineering Service ATTN: Nathan M. Newmark 1211 Civil Engineering Bldg. Urbana, IL 61801	es Departme ATTN: P Norman,	ety of Oklahoma ent of Physics Prof R. Fowler OK 73069
		Aberdeen Pro	ving Ground
1	University of Maryland Department of Physics ATTN: Dr. E. Oktay College Park, MD 20742 The University of Michigan Gas Dynamics Laboratory ATTN: Z. Gabrijel	Cdr, USATE ATTN: D	RXSY-D DRXSY-MP, H. Cohen
	Aerospace Engineering Bldg. Ann Arbor, MI 48109	Bldg E35	
1	The University of New Mexico Eric H. Wang Civil Engineering Research Facility ATTN: Technical Library University Station, Box 188 Albuquerque, NM 87131	S	

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet and return it to Director, US Army Ballistic Research Laboratory, ARRADCOM, ATTN: DRDAR-TSB, Aberdeen Proving Ground, Maryland 21005. Your comments will provide us with information for improving future reports.

1. BRL Report Number
2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)
3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.)
4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.
5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.)
6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.
Name:
Telephone Number:
Organization Address: